

## AVOCOR E SERIES DATASHEET

55" | 65" | 75" | 86"



## **OVERVIEW**

The new and improved E series displays utilize the very latest optimized touch technology, that supports up to 20 points of touch using Avocor Intelligent Touch, and superior optically bonded glass technology providing a smooth and extremely accurate, low latency writing experience as well as object recognition.

The ability to easily switch between using a pen, finger, and palm create for a fluid collaborative environment for users in real-time, with an array of front-facing guest connectivity options now including a Type-C\* connection along the Connect and Control bar, and features Avocor's UiQ touch enabled interface, enhancing the user experience and FUSE remote management, completely free-of-charge.

IDEAL FOR:







## **SOLUTION**

## Highlights



Avocor UiQ - smart touch enabled dynamic user interface.



Superior glass technology provides an extremely accurate writing experience.



Zero parallax optically bonded glass surface for pixel-perfect inking.



Type-C connectivity\* and enhanced HDMI out supporting 4K video @60Hz.



Front-facing soundbar delivering a crystal-clear audio experience.



FUSE - our free-of-charge cloudbased display & software management platform for AV/IT Managers.



Montage - wireless screen sharing from any device and instant white-boarding capabilities.



DISPLAY	AVE-5540	AVE-6540	AVE-7540	AVE-8640
Diagonal size (Inch)	55	65	75	86
Backlight	Direct-lit LED			
Aspect ratio	16:9			
Resolution	3840 x 2160 @ 60Hz			
Response time	8 ms			
Brightness	400 (cd/m2)			
Contrast ratio	4000:1			
Viewing angle	178° / 178°			
Supported colors	10 Bit 1.07 Billion Color			
Display orientation		Lands	cape	
TOUCH SYSTEM				
Interface	1 x Type-C, 2 x USB-B (1 x 2.0 +1 x 3.0)			
Touch	Up to 20 Point Avocor Intelligent Touch - supports 1 x fine tip stylus			
Glass	Zero parallax, bonded, anti-fingerprint glass			
Supported operating system	Windows 8 / 10; Mac OSX**; Linux**; Chrome			
CONNECTIVITY				
Guest inputs	1 x Type-C (45W PD), 1 x HDMI 2.0, 1 x USB-B touch,1 x USB-A 3.0 hub			
Side IO	2 x HDMI 2.0, 1 x DisplayPort 1.2, 1 x USB-B Touch, 1 x USB-A 3.0 Hub, 1 x USB-A 3.0 rub			
JIUC 10	2 x HDMI 2.0, 1 x DisplayPort 1.2, 1 x 036-6 Touch, 1 x 036-A 3.0 Hub, 1 x 036-A Service Port, 1 x HDMI Out (Support 4K@60Hz, 1920x1080@60Hz)			
Audio	1 x 3.5mm audio out, 1 x optical (SPDIF)			
Control	1 x RS-232, 1 x LAN Ethernet (RJ-45) in, 1 x LAN Ethernet (RJ-45) out			
OPS slot		Yes, 3840 x 2	160 @60Hz	
AUDIO & MICROPHONE				
Built-in speakers		2 x 20W - for	rward facing	
DISPLAY & REMOTE FUNCTI	ONE	2 / 2017 101	Wara racing	
Auto-source-detection	UNS	Vo		
Source preview	Yes Yes			
Blank	Yes Yes			
Freeze	Yes			
		ie	5	
PHYSICAL SPECIFICATIONS			l	
Product dimensions	1286 x 802 x 78.4 mm 50.63 x 31.57 x 3.09 in	1513 x 938 x 99.5 mm 59.57 x 36.93 x 3.92 in	1771 x 1071 x 112 mm 69.72 x 42.16 x 4.41 in	2018 x 1211 x 112 mm 79.45 x 47.68 x 4.41 in
Shipping dimensions	1421 x 932 x 216 mm 55.94 x 43.70 x 8.50 in	1649 x 1110 x 216 mm 64.92 x 43.70 x 8.50 in	1920 x 1240 x 270 mm 75.59 x 48.82 x 10.63 in	2170 x 1380 x 270 mm 85.43 x 48.82 x 10.63 ir
Weight	Net: 28 kgs   61.73 lbs Gross: 41 kgs   90.39 lbs	Net: 39 kgs   85.98 lbs Gross: 52 kgs   114.64 lbs	Net: 48.5 kgs   106.9 lbs Gross: 62 kgs   136.7 lbs	Net: 61.5 kgs   135.6 lbs Gross: 78 kgs   172 lbs
Wall mount (VESA)	400 x 400 mm   15.75 x 15.75 in	600 x 400 mm   23.62 x 15.75 in	800 x 400 mm	31.50 x 15.75 in
PC Mount	100 x 100 mm   3.94 x 3.94 in			
Handles	2	)		4
POWER				
Power supply		AC100-240V (wor	ldwide), 50/60Hz	
Max power consumption	<22	· ·	<300W	<320W
Standby	<2200V ≤0.5W			
ENVIRONMENTAL				
Operating temperature	0°C ~ 40°C			
Storage temperature	-20°C ~ 60°C			
Humidity	20% ~ 85%			
WHAT COMES IN THE BOX				
TTIAL COMES IN THE BOX	1D	- 0 · 0 · · · · · · · · · · · · · · · ·	-t-lu AC 1 /4 111	( 4 ELL 4 LIC 4 ALIC) 4
	1 X Remote control & batteries	s, 2 x 3mm fine-tip passive touch : 3m   118.1 in), 1 x HDMI cable (3)	styluses, AC power cords (1 x UK m   118.1 in). 1 x Tyne-C cable (1	., 1 x EU, 1 x US, 1 x AUS), 1 ; .8m   70.9 inches)









Terms and conditions vary via region, please <u>click here</u>









www.avocor.com

**Extended warranty** 

GroupShare
Secure and simple one
touch access to your ap

Avocor OPS
Seamless interoperabili

Protect

Additional remote

Additional stylus

