

AVOCOR A SERIES DATASHEET

65" | 75" | 86"

OVERVIEW

The Avocor A Series is designed to transform educational spaces into interactive and engaging environments, supporting both in-person and distance learning. With its EDLA certification, the A Series seamlessly integrates into educational ecosystems, enabling schools and universities to enhance student engagement and streamline remote instruction.

These displays are built for flexibility, with powerful 4K resolution, superior touch technology, and robust connectivity to meet the evolving needs of modern classrooms.

The A Series is equipped with a detachable 4K camera and advanced microphone array, ensuring remote students experience the same level of interaction as those physically present. This solution empowers educators to deliver immersive lessons that bridge the classroom and remote environments, fostering a more inclusive learning experience.

The A Series is the ultimate tool for modernizing education and creating impactful learning experiences for all students, no matter where they are.

SOLUTION Highlights



G 🖸

G

EDLA Certified

10:16

Access to the Google Play Store, allowing seamless installation of educational apps for enhanced learning and interaction.

J 💿

:::



Built for Distant Learning

With a detachable 4K camera and 10-microphone array, ensuring clear communication for remote students.



Advanced Touch Technology Supports up to 40 simultaneous touch points, making it ideal for interactive lessons.



Immersive 4K Displays Available in 65", 75", and 86" sizes, featuring zero air gap and anti-glare glass for enhanced touch accuracy



SPECIFICATIONS

DISPLAY	AVA-6520	AVA-7520	AVA-8620
Size	65"	75"	86"
Backlight	Direct-lit LED		
Aspect Ratio	16:9		
Resolution	3840x 2160 @ 60Hz		
Response Time	3.3 ms (1 Touch)		
Brightness (max w/glass)	500 (cd/m2)		
Contrast Ratio	1200:1		
/iewing Angle	178° / 178°		
Supported Colors	10-bit (D), 1.07 Billion colors		
Display Orientation	Landscape		
OUCH SYSTEM			
ouch Points	40 Multi-touch points		
Blass	Zero bond, anti-fingerprint, double-sided anti-glare		
upported OS	Android 13.0		
PU			
PU	A76x4 + A55x4		
iPU	Mali-G610 MC4		
AM/ROM	RAM/ROM 8 GB/128 GB		
ndroid version	Android 13		
ONNECTIVITY			
ront Inputs	Type C (DP Alt-mode, USB, 15W PD) x 1, HDMI 2.0 x 1, USB-B 2.0 x 1, USB-A 3.0 x 3		
	MIC in (3.5mm) x 1, Line out (3.5mm) x 1, S/PDIF x 1, RS232c (D-Sub9) x 1, HDMI 2.1 out x 1,		
Bottom Inputs	Type C (15W PD) out x 1, LAN x 2, USB-A 3.0 (Android only)		
ide IO	HDMI 1.4b x 1, HDMI 2.0 x 2, USB-B 3.0 (for touch), Type C (DP Alt-mode, USB, 65W PD) x 1, USB-A 3.0 x 1, USB-A 2.0 x 2, DP x 1, SD CARD x 1		
udio	MIC IN (3.5 mm), RS232c x 1, LINE OUT (3.5 mm) x 1, S/PDIF x 1		
iontrol	1 x RS232c, 2 x LAN Ethernet (RJ-45)		
DPS Slot	Yes		
ViFi	WiFi 5.0		
NUDIO			
Built-in Speakers	2.1 Channel (2 x 16W speakers + 20W subwoofer)		
And the speakers	10-element linear isometric array, omnidirectional with 8m pickup range, noise and echo cancellation		
	Detachable 4K camera, 13MP Sony IMX214 sensor, 123° field of view, fixed focus at 2m, 30fps, with 2D/3D noise reduction,		
Camera	Betachable in camera, form bony	auto white balance, and exposure regulation	oorps, with 20,00 holse reduction,
PHYSICAL SPECIFICATIONS			
creen Dimensions (L x W x H)	1499 x 87 x 954 mm (59.02" x 3.43" x 37.5")	1721 x 87 x 1079 mm (67.72" x 3.43" x 42.48")	1967 x 87 x 1218 mm (77.48" x 3.43" x 48.03")
hipping Dimensions (L x W x H)	1613 x 216 x 1050 mm (63.47" x 8.50" x 41.34")	1830 x 216x 1175 mm (72.05" x 8.50" x 46.38")	2071 x 216 x 1317 mm (81.54" x 8.50" x 51.85"
	3 mm all sides		
ezel Dimensions Veight (Net)	40 kg (00 5 lbs)		70 kg (454 lbs)
Veight (Gross)	42 kg (92.5 lbs) 54 kg (119 lbs)	56 kg (123 lbs) 70 kg (154 lbs)	70 kg (154 lbs) 86 kg (189 lbs)
Vall Mount (VESA)	500 x 400 (mm), M8 Screw	600 x 400 (mm), M8 Screw	800 x 400 (mm), M8 Screw
	500 X 400 (mm), Mo Sciew		000 X 400 (IIIII), MO SCIEW
PC Mount landles	None 2		
ENSORS		Δ	
		IR	
ower		Л	
fax Power Consumption	Tetal <- 20014/	Total <= 330W	Tatal <= 440\M/
· · · ·	Total <= 280W	IOLAI <= 350VV	Total <= 440W
		0°C to 40°C	
Operating Temperature			
torage Temperature	-20°C to 60°C		
lumidity		20% to 85%	
VHAT COMES IN THE BOX	4 5 4 114/11 116		
	1 x Remote control, Wall mount, AC power cord, 1 x	USB-A/B 2.0 cable, 1 x HDMI cable, 1 x Quick Start Guid	1e, NFC card x 2, eraser x 1, stylus x 2, extra stylus ti

